Revision: 08.08.2012 Printing date 08.08.2012

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: OTTOSEAL M 360

· Application of the substance / the preparation Spacings sealent

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Hermann Otto GmbH Krankenhausstraße 14 D-83413 Fridolfing Tel.: 0049/(0)8684/908-0

Fax.: 0049/(0)8684/908-539

· Further information obtainable from:

Tel.: 0049- (0)8684- 908- 641 (-460) E-Mail: alois.parzinger@otto-chemie.de

· Emergency telephone number: Tel.: 0049- (0)89- 192 40 (emergency telephone no.)

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC not applicable
- · Information concerning particular hazards for human and environment:

Preparation is not hazardous in terms of directive 1999/45/EU.

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

Observe the general safety regulations when handling chemicals

The product is not subject to identification regulations under EU Directives and the Ordinance on Hazardous Materials (German GefStoffV).

· Special labelling of certain preparations:

Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction. Safety data sheet available for professional user on request.

- Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Sealant based on silane-terminated polymers (hybrid)
- **Dangerous components:**

CAS: 2768-02-7 trimethoxyvinylsilane < 2.5%

EINECS: 220-449-8 Xn R20

R10

CAS: 16753-62-1 Dimethoxymethylvinylsilan < 2.5%

EINECS: 240-816-6 K F R11

· Additional information For the wording of the listed risk phrases refer to section 16.

Printing date 08.08.2012 Revision: 08.08.2012

Trade name: OTTOSEAL M 360

(Contd. of page 1)

4 First aid measures

- · Description of first aid measures
- After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Do not induce vomiting; call for medical help immediately. Show container or label.

Rinse out mouth and then drink plenty of water in small amounts (if person is conscious).

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- Protective equipment:

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Ensure adequate ventilation
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Pick up mechanically.

· Reference to other sections See Section 8 for information on personal protection equipment.

7 Handling and storage

- · Handling
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

see item 8: Personal protective equipment

- · Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and receptacles:

Prevent any seepage into the ground.

- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 3)

Printing date 08.08.2012 Revision: 08.08.2012

Trade name: OTTOSEAL M 360

Protect from heat and direct sunlight.

(Contd. of page 2)

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:
- CAS No. Designation of material % Type Value Unit
- Additional Occupational Exposure Limit Values for possible hazards during processing:

67-56-1 methanol

OES Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm

Sk, ILV

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment
- General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Protection of hands: Protective gloves.
- · Material of gloves

Natural rubber, NR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

- · Eye protection: Safety glasses
- · Body protection: Protective work clothing.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:

pasty

Colour:

According to product specification

· Odour:

Characteristic

· Change in condition

Melting point/Melting range: undetermined

· Self-igniting:

Product is not selfigniting.

Danger of explosion:

Product does not present an explosion hazard.

· Density at 20°C:

1.42 g/cm³

· Solubility in / Miscibility with

Water:

Not miscible or difficult to mix

GB -

Printing date 08.08.2012 Revision: 08.08.2012

Trade name: OTTOSEAL M 360

(Contd. of page 3)

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Avoid strong heating.

- · Possibility of hazardous reactions No dangerous reactions known
- · Hazardous decomposition products: see item 5.3

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Irritating effects to skin and mucous membranes possible
- on the eye: Irritating effect possible
- Other information (about experimental toxicology):

In curing the material splits off a small amount of methanol.

After curing the material is odourless and completely harmless.

· Additional toxicological information:

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

12 Ecological information

- Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability
- Other information: The product is difficultly biodegradable.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Observe local by-laws.

Already cured material can be disposed of with the domestic or commercial waste. Unconsumed material (fluid, paste-like) is to dispose of as hazardous waste.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

cleaning.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

GB

Printing date 08.08.2012 Revision: 08.08.2012

Trade name: OTTOSEAL M 360

(Contd. of page 4)

14 Transport information

· UN-Number

· ADR, ADN, IMDG, IATA Void

· UN proper shipping name

· ADR, ADN, IMDG, IATA Void

· Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· Packing group

· ADR, IMDG, IATA Void

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

• Transport/Additional information: Not dangerous according to the above

specifications.

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

R10 Flammable.

R11 Highly flammable.

R20 Harmful by inhalation.

- Department issuing MSDS: Tel.: 0049- (0)8684- 908- 641
- Contact: Tel.: 0049- (0)8684- 908- 641 (-460)
- * Data compared to the previous version altered.

GB